

UATS-DR (82x18 Displayed)

Utility Style, Aluminum Frame, Tandem Axle, Solid side Trailer with Drop in Side Ramps



-Standard Features and Equipment-

-6061 All Aluminum Frame	-2x10 Douglas Fir/Larch Plank Floor
-13.5" Side Height (Deck to top of Flange)	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-Tandem 3500lb Drop Axles, Electric Brakes	-Folding Rear Ramp rated at 3000lbs
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Ramp Unfolded Length: 54" L x 77" W (Ramp Width is trailer size - 5.00")
-7-Pin RV Style Electrical Connector	-Ramp Folds Down onto Deck
-Junction Box, Break-away Kit with Battery and Charger	-Side Loading Access w/ Drop in Ramp Gates, 1250lb Capacity/Ea, 61" L x 13" W
-2-5/16" Ball Coupler, Max 2,100lb tongue WT, with Polypropylene Tape	-4,000lb Lashing Rings , ZP (6 rings on 14' models, 6 on 16', and 8 on 18')
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"
-LED Lighting Package	-Ground to Coupler Height: 15" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 7000lbs
-A-Frame Mounted Jack Rated at 5K lbs	

-Available Sizes-

Description	Payload	Dry Wt.
UATS-76x14-DR	5,605 lbs	1395 lbs
UATS-76x16-DR	5,570 lbs	1430 lbs
UATS-82x14-DR	5,520 lbs	1480 lbs
UATS-82x16-DR	5,420 lbs	1580 lbs
UATS-82x18-DR	5,320 lbs	1680 lbs

-Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Extra Lashing Rings 4k lb
Recessed Lashing Rings 6k lb
Jack Caster Wheel
Side Mount Pivot Jack
Stabilizer Stands, Drop Leg
2-5/16" Adjustable Coupler
A-Frame Mounted, Lockable Handle Tool Box

*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.