

Phone: (204) 364-2785 Email: sales@stronghaul.com

Address: 139144 Road 11E Arborg, MB, Canada

Box 269 R0C 0A0

## **EATF-DT** (10K or 14K GVW Available)

Equipment Hauler, Aluminum Frame, T and T and T and T and T are T are T are T and T are T are T are T are T are T and T are T are T are T are T are T and T are T and T are T and T are T and T are T



-Standard Features and Equipment-		
-8.00" x 3.00" x .250"w 6061-T6 Frame Tubes	-Modular-Style, Black Steel Wheels, R15", 6 lug on 5.5" BHP on -DT52 models	
-6.00" x 2.00" x .250"w 6061-T6 Hitch Tubes	-Modular-Style, Black Steel Wheels, R16", 8 lug on 6.5" BHP on -DT70 models	
-3.00" x 1.50" x .190"w 6061-T6 Floor Channels on 16" ctrs	-7-Way RV-Style Connector	
250" Stake Pockets (3.5"x1.5" ID)	-Junction Box, Break-away Kit w/Charger	
250" x 3.00" 6061-T6 Rub Rail	-LED Lighting Pkg with Reverse Lights	
-2' Dovetail Section, 3" Drop (Length of trailer includes DT section)	-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	
-5200lb Strt, E-brk, Slipper Leaf Spring, Dexter Axles on -DT52 models	-2x8 No.1 Grade, DglsFir/Larch Plank Floor	
-7000lb Strt, E-brk, Slipper Leaf Spring, Dexter Axles on -DT70 models	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch	
-HD Slipper Style Suspension, Greaseable Equalizer	-Tip Out Fenders with Stainless Latch	
-Brass Bushings in Leaf Spring Eyelet	-Fold Up Stabilizer Stands	
-Galvanized .250" Axle Mounting Brackets with Polypropylene Tape	-4k lb Lashing Rings, Zinc Plated (8 Rings on 20' model, 10 on 22'/24', 12 on 26')	
-2-5/16" Adjustable Ball Coupler, 4" of Height Adjustment	-Pocket Style Ramps, Mounts Under Rear of Deck, 7,000lb CAP/Ea, 78" L x 14" W	
-9,500lb, Drop Leg Jack with Removable Side Wind Handle	-Deck to Ground Height: 26"	
-13.5" Front Rail with Spare Tire Mount (side MNT if tool box installed)	-Bumper to Ground Height: 23"	
-ST225/75R15 6-ply Radial Tires on DT52 models	-Coupler to Ground Height: 16" When Level (18" or 14" with adjustment)	
-ST235/80R16 10-ply Radial Tires on -DT70 models	-Ramp Loading Angle: 15 Degrees	
	-GVWR: 14,000lbs or 10,000lbs (14K can be derated to 10K at time of registration)	

-Available Sizes-		
Description	Payload	Dry Wt.
EATF-82x20-DT52	8,170 lbs	1720 lbs
EATF-82x22-DT52	8,070 lbs	1820 lbs
EATF-82x24-DT52	7,970 lbs	1920 lbs
EATF-82x26-DT52	7,870 lbs	2020 lbs
EATF-82x20-DT70	12,080 lbs	1920 lbs
EATF-82x22-DT70	11,980 lbs	2020 lbs
EATF-82x24-DT70	11,880 lbs	2120 lbs
EATF-82x26-DT70	11,780 lbs	2220 lbs

-Available Options-		
Description		
Aluminum Wheel Upgrade PKG		
Spare Wheel, Steel		
Spare Wheel, Aluminum		
Extra Lashing Rings 4k lb		
Recessed Lashing Rings 6k lb		
12" x 18" Winch Plate		
A-Frame Mounted, Lockable Handle Tool Box		