

Phone: (204) 364-2785 Email: <u>sales@stronghaul.com</u> Address: 139144 Road 11E Arborg, MB, Canada Box 269 ROC 0A0

FATD (7K or 10K GVW)

Flat deck Style, **A**luminum Frame, **T**andem, **D**eck over Axle Trailer



-Standard Features and Equipment-

-6061 All Aluminum Frame	-2x8 Douglas Fir/Larch Plank Floor	
-3500lb Straight Axles, Elec. Brakes (Changes to 5200lb axles on -52 models)	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch	
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Folding Rear Ramp rated at 3000lbs	
-7-Pin RV Style Electrical Connector	-Pocket Style Ramps, Mounts under Rear of Deck, 2,500lb CAP/Ea 78" L x 14" W	
-Junction Box, Break-away Kit with Battery and Charger	-Stake Pockets and Side Rub Rail All Around	
-2-5/16" Ball Coupler, Max rating 2,100lb tongue WT, with Polypropylene Tape	-4,000lb Lashing Rings, ZP (6 rings on 14' models, 6 on 16', and 8 on 18')	
-ST205/75R15 6-ply Radial Tires (ST225/75R15 7-ply tires for -52 models)	-Spare Tire Mount (Changes from front to side depending on tool box)	
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black (6 on 5.5" for -52)	-Deck to Ground Height: 30"	
-LED Lighting Package	-Ground to Coupler Height: 17" When Level	
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 7000lbs on -35 models (9,980lbs on -52 models)	
-A-Frame Mounted Jack Rated at 5K lbs		

-Available Sizes -35 Models-			
Description	Payload	Dry Wt.	
FATD-101x14-35	5,470 lbs	1530 lbs	
FATD-101x16-35	5,400 lbs	1600 lbs	
FATD-101x18-35	5,285 lbs	1715 lbs	
FATD-101x20-35	5,195 lbs	1805 lbs	

-Available Sizes -52 Models-		
Description	Payload	Dry Wt.
FATD-101x14-52	8,205 lbs	1685 lbs
FATD-101x16-52	8,130 lbs	1760 lbs
FATD-101x18-52	8,020 lbs	1870 lbs
FATD-101x20-52	7,925 lbs	1965 lbs

-Available Options-	
Description	
Aluminum Wheel Upgrade PKG	
Spare Wheel, Steel	
Spare Wheel, Aluminum	
Extra Lashing Rings 4k lb	
Recessed Lashing Rings 6k lb	
Jack Caster Wheel	
Side Mount Pivot Jack	
2-5/16" Adjustable Coupler	
Front Rail Kit, Bolt In	
A-Frame Mounted, Lockable Handle Tool Box	