

FATD (101x20 Displayed)

Flat deck Style, Aluminum Frame, Tandem, Deck over Axle Trailer



-Standard Features and Equipment-

-6061 All Aluminum Frame	-2x8 Douglas Fir/Larch Plank Floor
-3500lb Straight Axles, Elec. Brakes (Changes to 5200lb axles on -52 models)	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Folding Rear Ramp rated at 3000lbs
-7-Pin RV Style Electrical Connector	-Pocket Style Ramps, Mounts under Rear of Deck, 2,500lb CAP/Ea 78" L x 14" W
-Junction Box, Break-away Kit with Battery and Charger	-Stake Pockets and Side Rub Rail All Around
-2-5/16" Ball Coupler, Max rating 2,100lb tongue WT, with Polypropylene Tape	-4,000lb Lashing Rings , ZP (6 rings on 14' models, 6 on 16', and 8 on 18')
-ST205/75R15 6-ply Radial Tires (ST225/75R15 7-ply tires for -52 models)	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, White (6 on 5.5" for -52)	-Deck to Ground Height: 30"
-LED Lighting Package	-Ground to Coupler Height: 17" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 7000lbs on -35 models (9,900lbs on -52 models)
-A-Frame Mounted Jack Rated at 5K lbs	

-Available Sizes -35 Models-

Description	Payload	Dry Wt.
FATD-101x14-35	5,405 lbs	1595 lbs
FATD-101x16-35	5,057 lbs	1943 lbs
FATD-101x18-35	4,709 lbs	2291 lbs
FATD-101x20-35	4,360 lbs	2640 lbs

-Available Sizes -52 Models-

Description	Payload	Dry Wt.
FATD-101x14-52	8,345 lbs	1645 lbs
FATD-101x16-52	7,997 lbs	1993 lbs
FATD-101x18-52	7,649 lbs	2341 lbs
FATD-101x20-52	7,301 lbs	2689 lbs

-Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Extra Lashing Rings 4k lb
Recessed Lashing Rings 6k lb
Jack Caster Wheel
Side Mount Pivot Jack
2-5/16" Adjustable Coupler
Front Rail Kit, Bolt In
A-Frame Mounted, Lockable Handle Tool Box

*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.