

Phone: (204) 364-2785 Email: sales@stronghaul.com

Address: 139144 Road 11E Arborg, MB, Canada

Box 269 R0C 0A0

SASD-TD

 $oldsymbol{\mathsf{S}}$ nowmobile Style, $oldsymbol{\mathsf{A}}$ luminum Frame, $oldsymbol{\mathsf{S}}$ ingle Axle, $oldsymbol{\mathsf{D}}$ eck over Axle, $oldsymbol{\mathsf{T}}$ ilt $oldsymbol{\mathsf{D}}$ eck







-Standard Features and Equipment-		
Deck Size: 102" W x 120" L	Lighting: LED Lighting Package	
Overall Size: 102" W x 164" L	Harness: Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	
GVWR: 2,990lb (may be increased to 3,500lb with Electric Brake option)	Jack: 5,000lb Cap, Side Mount, Pivot Jack, ZP	
Deck to GND Height: 30"	Decking: 3/4" Douglas Fir/Larch Plywood	
Coupler to GND Height: 22"	Safety Chains: 5/16" x 30", 7,600lb Rating per Chain, S-Hook w/ Safety Latch, ZP	
Frame Tubes: 3.00" x 2.00" x .125" 6061-T6	Lashing Rings: 6 x 2,000lb WLL Lashing Rings, 3/8 Dia, ZP	
Hitch Tubes: 3.00" x 2.00" x .188" 6061-T6	Ski-Tie Bar: 2 x Super-clamp Hold Down Bars, with 24" Adjustable Super-trac Kit	
Cross members: 2.50" x 1.25" x .125" 6061-T6 on 24" centers	Loading: 30 Degree Loading Angle, Tilt Deck	
Axle: Dexter 3500lb Leaf Sprung, Idler Axle	Spare Tire Mount: Underside Spare Tire Holder	
Coupler: 2" Ball, A-frame Style, Zinc Plated, with Polypropylene Isolation Tape	Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	
Tires: Goodride or Westlake ST205/75R15 6-ply Radial Tires	Features: Laser Cut Side Rails/Anchor Points	
Wheels: Black Modular Style Wheels, R15" x 6" W, 5 Lug on 4.5" BHP	Cushioned deck landing, rubber bumper and gas strut	
Harness Plug: 4-Flat, Easy-Pull, Electrical Connector		

-Availab	ole Sizes -	
Description	Payload	Dry Wt.
SASD-101x10-TD	2,340 lbs	650 lbs

-Available Options-
Description
Aluminum Wheel Upgrade Package
Spare Wheel, Aluminum
Spare Wheel, Steel
Super-glide Decking Upgrade
Downward Deflecting Spray Shield
Tool Box, Lockable Handle
Electric Braking Axle Upgrade