

UASS (60x10 Displayed)

Utility Style, Aluminum Frame, Single Axle, Solid side Trailer



-Standard Features and Equipment-

-6061 All Aluminum Frame	-2x10 Douglas Fir/Larch Plank Floor
-13.5" Side Height (Deck to top of Flange)	-5/16" x 30" Safety Chains, 7.6K lb Rating, with Safety Latch
-3500lb Straight Axle, Idler	-Folding Rear Ramp rated at 3000lbs
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Ramp Unfolded Length: 54" L x 55" W (Ramp Width is trailer size - 5.00")
-4-Pin Flat, Easy Pull Electrical Connector	-Ramp Folds Down onto Deck
-2" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape	-2,000lb Lashing Rings , ZP (4 rings on 8' models, 6 on 10', 8 on 12', and 10 on 14')
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"
-LED Lighting Package	-Ground to Coupler Height: 15" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 2,990lbs (3,500lbs with additional electric brake option)
-A-Frame Mounted Jack Rated at 5K lbs	

-Available Sizes-

Description	STD. Payload	Dry Wt.
UASS-60x08	2,435 lbs	555 lbs
UASS-60x10	2,370 lbs	620 lbs
UASS-60x12	2,340 lbs	650 lbs
UASS-66x08	2,370 lbs	620 lbs
UASS-66x10	2,340 lbs	650 lbs
UASS-66x12	2,250 lbs	740 lbs
UASS-76x10	2,245 lbs	745 lbs
UASS-76x12	2,205 lbs	785 lbs
UASS-76x14	2,035 lbs	955 lbs
UASS-82x12	2,075 lbs	840 lbs
UASS-82x14	2,030 lbs	960 lbs

-Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Spray Shield, Solid Side, 60"
Spray Shield, Solid Side 66"
Spray Shield, Solid Side 76"
Spray Shield, Solid Side 82"
Drop In Rear Panel, 60"
Drop In Rear Panel, 66"
Drop In Rear Panel, 76"
Drop In Rear Panel, 82"
Extra Lashing Rings 2k lb
Jack Caster Wheel
Side Mount Pivot Jack
A-Frame Mounted, Lockable Handle Tool Box
Electric Braking Axle Upgrade