

UASS-DR (76x12 Displayed)

Utility Style, **A**luminum Frame, **S**ingle Axle, **S**olid side Trailer with **D**rop in Side **R**amps



-Standard Features and Equipment-

-6061 All Aluminum Frame	-2x10 Douglas Fir/Larch Plank Floor
-13.5" Side Height (Deck to top of Flange)	-5/16" x 30" Safety Chains, 7.6K lb Rating, with Safety Latch
-3500lb Drop Axle, Idler	-Folding Rear Ramp rated at 3000lbs
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Ramp Unfolded Length: 54" L x 55" W (Ramp Width is trailer size - 5.00")
-4-Pin Flat, Easy Pull Electrical Connector	-Ramp Folds Down onto Deck
-2" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape	-Side Loading Access w/ Drop in Ramp Gates, 1250 lb Capacity/Ea, 61" L x 13" W
-ST205/75R15 6-ply Radial Tires	-2,000lb Lashing Rings , ZP (8 rings on 12' models, and 10 on 14')
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, White	-Spare Tire Mount (Changes from front to side depending on tool box)
-LED Lighting Package	-Deck to Ground Height: 18"
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-Ground to Coupler Height: 15" When Level
-A-Frame Mounted Jack Rated at 5K lbs	-GVWR: 2,990lbs (3,500lbs with additional electric brake option)

-Available Sizes-

Description	STD. Payload	Dry Wt.
UASS-76x12-DR	2,040 lbs	950 lbs
UASS-76x14-DR	1,950 lbs	1040 lbs
UASS-82x12-DR	1,979 lbs	1020 lbs
UASS-82x14-DR	1,700 lbs	1290 lbs

-Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Extra Lashing Rings 2k lb
Jack Caster Wheel
Side Mount Pivot Jack
A-Frame Mounted, Lockable Handle Tool Box
Electric Braking Axle Upgrade

*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.