

UATF (82x18 Displayed)

Utility Style, Aluminum Frame, Tandem Axle, Flat Bed Trailer



-Standard Features and Equipment-

-6061 All Aluminum Frame	-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone
-13.5" Front Rail Height (Deck to top of Rail)	-A-Frame Mounted Jack Rated at 5K lbs
-3500lb Drop Axles, Elec. Brakes (Changes to 5200lb Straight axles on -52 models)	-2x8 Douglas Fir/Larch Plank Floor
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-7-Pin RV Style Electrical Connector	-Stake Pockets and Side Rub Rails, Removable Fenders
-Junction Box, Break-away Kit with Battery and Charger	-4k lb Lashing Rings, ZP (6 rings on 12' models, 6 on 14', 6 on 16', and 8 on 18')
-2-5/16" Ball Coupler, Max 2,100lb tongue WT, with Polypropylene Tape	-Spare Tire Mount (Changes from front to side depending on tool box)
-ST205/75R15 6-ply Radial Tires (ST225/75R15 7-ply tires for -52 models)	-Deck to Ground Height: 19" on -35 models (23" on -52 models)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, White (6 on 5.5" for -52)	-Ground to Coupler Height: 16" When Level (both models)
-LED Lighting Package	-GVWR: 7000lbs on -35 models (9,990lbs on -52 models)

-Standard Ramp Specs-

-Pocket Style Ramps, Mounts Under Rear of Deck, 2,500lb CAP/Ea, 78" L x 14" W-
-Folding Rear Bi-Fold Ramp, Rated at 3000lbs, 54" L x 77" W (Ramp Width is trailer size -5.00" for fold down purposes)-

-Available Sizes w/ Pocket Style Ramp-

Description	Payload	Dry Wt.
UATF-82x12-35	5,800 lbs	1200 lbs
UATF-82x14-35	5,640 lbs	1360 lbs
UATF-82x16-35	5,560 lbs	1440 lbs
UATF-82x18-35	5,500 lbs	1500 lbs
UATF-82x12-52	8,540 lbs	1450 lbs
UATF-82x14-52	8,380 lbs	1610 lbs
UATF-82x16-52	8,300 lbs	1690 lbs
UATF-82x18-52	8,240 lbs	1750 lbs

-Available Sizes w/ Bi-fold Ramp-

Description	Payload	Dry Wt.
UATF-82x12-35-B	5,800 lbs	1200 lbs
UATF-82x14-35-B	5,640 lbs	1360 lbs
UATF-82x16-35-B	5,560 lbs	1440 lbs
UATF-82x18-35-B	5,500 lbs	1500 lbs
UATF-82x12-52-B	8,540 lbs	1450 lbs
UATF-82x14-52-B	8,380 lbs	1610 lbs
UATF-82x16-52-B	8,300 lbs	1690 lbs
UATF-82x18-52-B	8,240 lbs	1750 lbs

-Available Options for Both Ramp Styles-

Description	Description
Aluminum Wheel Upgrade PKG	Jack Caster Wheel
Spare Wheel, Steel	Side Mount Pivot Jack
Spare Wheel, Aluminum	Stabilizer Stands, Drop Leg
Spray Shield, 82"	2-5/16" Adjustable Coupler
Extra Lashing Rings 4k lb	12" x 18" Winch Plate
Recessed Lashing Rings 6k lb	Rail Cover (Stone Shield 15")
	A-Frame Mounted, Lockable Handle Tool Box

*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.