

UATF (7K or 10K GVW Available)

Utility Style, Aluminum Frame, Tandem Axle, Flat Bed Trailer



-Standard Features and Equipment-

-6061 All Aluminum Frame	-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone
-13.5" Front Rail Height (Deck to top of Rail)	-A-Frame Mounted Jack Rated at 5K lbs
-3500lb Strt, Leaf Spring Axles, Elec. Brakes on -35 models	-2x8 Douglas Fir/Larch Plank Floor
-5200lb Strt, Leaf Spring Axles, Elec. Brakes on -52 models (Torsions on 20' model)	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Stake Pockets and Side Rub Rails, Removable Fenders
-7-Pin RV Style Electrical Connector	-4k lb Lashing Rings, ZP(6 rings on 12',14',16' models, 8 rings on 18',20' models)
-Junction Box, Break-away Kit with Battery and Charger	-Spare Tire Mount (Changes from front to side depending on tool box)
-2-5/16" Ball Coupler, Max 2,100lb tongue WT, with Polypropylene Tape	-Deck to Ground Height: 23"
-ST205/75R15 6-ply Radial Tires (ST225/75R15 7-ply tires for -52 models)	-Ground to Coupler Height: 16" When Level (both models)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black (6 on 5.5" for -52)	-GVWR: 7000lbs on -35 models (9,980lbs on -52 models)
-LED Lighting Package	

-Standard Ramp Specs-

-Pocket Style Ramps, Mounts Under Rear of Deck, 2,500lb CAP/Ea, 78" L x 14" W-
-Folding Rear Bi-Fold Ramp, Rated at 3000lbs, 54" L x 77" W (Ramp Width is trailer size -5.00" for fold down purposes)-

-Available Sizes w/ Pocket Style Ramp-

Description	Payload	Dry Wt.
UATF-82x12-35	5,905 lbs	1095 lbs
UATF-82x14-35	5,830 lbs	1170 lbs
UATF-82x16-35	5,715 lbs	1285 lbs
UATF-82x18-35	5,620 lbs	1380 lbs
UATF-82x12-52	8,665 lbs	1225 lbs
UATF-82x14-52	8,595 lbs	1295 lbs
UATF-82x16-52	8,470 lbs	1420 lbs
UATF-82x18-52	8,390 lbs	1500 lbs

-Available Sizes w/ Bi-fold Ramp-

Description	Payload	Dry Wt.
UATF-82x12-35-B	5,905 lbs	1095 lbs
UATF-82x14-35-B	5,840 lbs	1160 lbs
UATF-82x16-35-B	5,730 lbs	1270 lbs
UATF-82x18-35-B	5,625 lbs	1375 lbs
UATF-82x12-52-B	8,660 lbs	1230 lbs
UATF-82x14-52-B	8,590 lbs	1300 lbs
UATF-82x16-52-B	8,470 lbs	1420 lbs
UATF-82x18-52-B	8,380 lbs	1510 lbs

-Available Options for Both Ramp Styles-

Description	Description
Aluminum Wheel Upgrade PKG	Jack Caster Wheel
Spare Wheel, Steel	Side Mount Pivot Jack
Spare Wheel, Aluminum	Stabilizer Stands, Drop Leg
Spray Shield, 82"	2-5/16" Adjustable Coupler
Extra Lashing Rings 4k lb	12" x 18" Winch Plate
Recessed Lashing Rings 6k lb	Rail Cover (Stone Shield 15")
	A-Frame Mounted, Lockable Handle Tool Box