

UATF-DT (82x20 Displayed, AKA 82x18+2)

Utility Style, Aluminum Frame, Tandem Axle, Flat Bed Trailer with 2' Dove Tail



-Standard Features and Equipment-

-6061 All Aluminum Frame	-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone
-2' Dovetail Section, 3" Drop (Length of trailer includes DT section)	-A-Frame Mounted Jack Rated at 5K lbs
-13.5" Front Rail Height (Deck to top of Rail)	-2x8 Douglas Fir/Larch Plank Floor
-3500lb Strt, Leaf Spring Axles, Elec. Brakes on -35 models	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-5200lb Strt, Leaf Spring Axles, Elec. Brakes on -52 models (Torsions on 22' model)	-Stake Pockets and Side Rub Rails, Removable Fenders
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-4k lb Lashing Rings, ZP(6 rings on 16' models, 8 rings on 18',20',22' models)
-7-Pin RV Style Electrical Connector	-Spare Tire Mount (Changes from front to side depending on tool box)
-Junction Box, Break-away Kit with Battery and Charger	-Deck to Ground Height: 23" (both 3500lb and 5200lb models)
-2-5/16" Ball Coupler, Max 2,100lb tongue WT, with Polypropylene Tape	-Bumper to Ground Height: 20" (both 3500lb and 5200lb models)
-ST205/75R15 6-ply Radial Tires (ST225/75R15 7-ply tires for -DT52 models)	-Ground to Coupler Height: 16" When Level (both 3500lb and 5200lb models)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black (6 on 5.5" for -DT52)	-GVWR: 7000lbs on -DT35 models (9,980lbs on -DT52 models)
-LED Lighting Package	

-Standard Ramp Specs-

-Pocket Style Ramps, Mounts Under Rear of Deck, 2,500lb CAP/Ea, 78" L x 14" W-
-Folding Rear Bi-Fold Ramp, Rated at 3000lbs, 54" L x 77" W (Ramp Width is trailer size -5.00" for fold down purposes)-

-Available Sizes w/ Pocket Style Ramp-

Description	Payload	Dry Wt.
UATF-82x16-DT35	5,450 lbs	1550 lbs
UATF-82x18-DT35	5,400 lbs	1600 lbs
UATF-82x20-DT35	5,350 lbs	1650 lbs
UATF-82x16-DT52	8,340 lbs	1650 lbs
UATF-82x18-DT52	8,290 lbs	1700 lbs
UATF-82x20-DT52	8,240 lbs	1750 lbs
UATF-82x22-DT52	8,185 lbs	1805 lbs

-Available Sizes w/ Bi-fold Ramp-

Description	Payload	Dry Wt.
UATF-82x16-DT35-B	5,450 lbs	1550 lbs
UATF-82x18-DT35-B	5,400 lbs	1600 lbs
UATF-82x20-DT35-B	5,350 lbs	1650 lbs
UATF-82x16-DT52-B	8,340 lbs	1650 lbs
UATF-82x18-DT52-B	8,290 lbs	1700 lbs
UATF-82x20-DT52-B	8,240 lbs	1750 lbs

-Available Options for Both Ramp Styles-

Description	Description
Aluminum Wheel Upgrade PKG	Jack Caster Wheel
Spare Wheel, Steel	Side Mount Pivot Jack
Spare Wheel, Aluminum	Stabilizer Stands, Drop Leg
Spray Shield, 82"	2-5/16" Adjustable Coupler
Extra Lashing Rings 4k lb	12" x 18" Winch Plate
Recessed Lashing Rings 6k lb	Rail Cover (Stone Shield 15")
	Lockable Handle Tool Box

*Note: Payload is an estimated amount and actual may vary, refer to VIN tag for more info.