

Phone: (204) 364-2785 Email: sales@stronghaul.com

Address: 139144 Road 11E Arborg, MB, Canada

Box 269 R0C 0A0

UATR-DR (82x16 Displayed)

 $m{U}$ tility Style, $m{A}$ luminum Frame, $m{T}$ andem Axle, $m{R}$ ailside Trailer with $m{D}$ rop in Side $m{R}$ amps



-Standard Features and Equipment-		
-6061 All Aluminum Frame	-2x10 Douglas Fir/Larch Plank Floor	
-13.5" Side Height (Deck to top of Rail)	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch	
-Tandem 3500lb Drop Axles, Electric Brakes	-Folding Rear Ramp rated at 3000lbs	
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Ramp Unfolded Length: 54" L x 71" W (Ramp Width is trailer size - 5.00")	
-7-Pin RV Style Electrical Connector	-Ramp Folds Down onto Deck	
-Junction Box, Break-away Kit with Battery and Charger	-Side Loading Access w/ Drop in Ramp Gates, 1250lb Capacity/Ea, 61" L x 13" W	
-2-5/16" Ball Coupler, Max 2,100lb tongue WT, with Polypropylene Tape	-4,000lb Lashing Rings , ZP (6 rings on 14' models, 6 on 16', and 8 on 18')	
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)	
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"	
-LED Lighting Package	-Ground to Coupler Height: 15" When Level	
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 7000lbs	
-A-Frame Mounted Jack Rated at 5K lbs		

-Available Sizes-		
Description	Payload	Dry Wt.
UATR-76x14-DR	5,820 lbs	1180 lbs
UATR-76x16-DR	5,715 lbs	1285 lbs
UATR-82x14-DR	5,780 lbs	1220 lbs
UATR-82x16-DR	5,700 lbs	1300 lbs
UATR-82x18-DR	5,540 lbs	1460 lbs

-Available Options-
Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Extra Lashing Rings 4k lb
Recessed Lashing Rings 6k lb
Jack Caster Wheel
Side Mount Pivot Jack
Stabilizer Stands, Drop Leg
2-5/16" Adjustable Coupler
12" x 18" Winch Plate
A-Frame Mounted, Lockable Handle Tool Box