



EATD

THE ALUMINUM ADVANTAGE

- ✓ Lightweight
- ✓ Fuel Economy
- ✓ Easier Handling
- ✓ Rust Resistant
- ✓ Paint Free
- ✓ Clean Aluminum Design



SMART DESIGN
Purpose Built • Work Ready



EATD



Address: 139144 Road 11E
Arborg, MB, Canada
P.O. Box 269 R0C 0A0

www.stronghaul.com



EATD

**Equipment Hauler,
Aluminum Frame, Tandem OR
Triple Axle, Deck Over Trailer**



EATD-101x23-14K

EATD-101x23-21K

EATD-101x25-14K

EATD-101x25-21K

EATD-101x27-14K

EATD-101x27-21K

EATD-101x29-14K

EATD-101x29-21K

PREMIUM ALUMINUM TRAILERS
Built for Work or Play

Available Sizes

Description	Payload	Dry Weight
EATD-101x23-14K	10,635 lbs	3,365 lbs
EATD-101x25-14K	10,535 lbs	3,465 lbs
EATD-101x27-14K	10,435 lbs	3,565 lbs
EATD-101x29-14K	10,335 lbs	3,665 lbs
EATD-101x23-21K	17,445 lbs	3,555 lbs
EATD-101x25-21K	17,335 lbs	3,665 lbs
EATD-101x27-21K	17,220 lbs	3,780 lbs
EATD-101x29-21K	17,110 lbs	3,890 lbs



ALL ALUMINUM CONSTRUCTION
Light • Strong • Durable

www.stronghaul.com

Standard Features

Frame: Aluminum 6061
Frame and Hitch Tubes: 8" x 3" x .25"w
Hitch Length: 63" L
Winch track: Double L Winch Track
Axle: 7000lb Straight, E-brake, Slipper Leaf Spring
Axle Brackets: .250" Galvanized and Taped
Harness Plug: 7-Way RV-Style Connector with Break-away Kit
Coupler: 2-5/16" Ball Coupler, 8" of adjustment, with Polypropylene Tape
Tires: Goodride or Westlake ST235/80R16 10-ply Radial Tires
Wheels: Black Mod. Steel, R16", 8 lug on 6.5" BHP
Lighting: LED Lighting Pkg with Sealed Harness
Jack: 9,500lb, Drop Leg with Removable Handle
Decking: 2x10 No. 1 Gr, Douglas Fir/Larch Planks
Safety Chains: 3/8" x 35" Chains, 16.2K lb Rating or 26.4K lb Rating
Ramp Loading Angle: 15 Degrees
Beavertail: 5' Beavertail Section, 16" Drop (Trailer Length includes Beavertail)
Deck Hatch: Rear Central Hatch, Lifts Between Ramps to be Level with Deck Surface
Ramps: Dual Flip Over Beaver Tail Ramps, 8,000lb
Integrated Ramp Knee Brace, Spring Assisted
Front Guard: 8" Front Lip/ Stone Guard
Spare Tire Mount: Front, or on side with toolbox
Deck to Ground Height: 35"
Ground to Coupler Height: 19" When Level
GVWR: 10,000lb (Derated), 14,000lb or 21,000lb

Available Options

- Aluminum Wheel Upgrade PKG
- Spare Wheel, Black Steel
- Spare Wheel, Aluminum
- Extra Lashing Rings 4k lb
- Recessed Lashing Rings 6k lb
- Toolbox, A-Frame Mounted, Lockable



PREMIUM ALUMINUM TRAILERS
Built for Work or Play