



EATF-DT

THE ALUMINUM ADVANTAGE

- ✓ Lightweight
- ✓ Fuel Economy
- ✓ Easier Handling
- ✓ Rust Resistant
- ✓ Paint Free
- ✓ Clean Aluminum Design



SMART DESIGN

Purpose Built • Work Ready



EATF-DT



Address: 139144 Road 11E
Arborg, MB, Canada
P.O. Box 269 R0C 0A0

www.stronghaul.com



EATF-DT

Equipment Hauler, Aluminum
Frame, Tandem Axle, Flat Bed
Trailer with 2' Dove Tail



EATF-82x20-DT-10K	EATF-82x20-DTB-10K
EATF-82x22-DT-10K	EATF-82x22-DTB-10K
EATF-82x24-DT-10K	EATF-82x24-DTB-10K
EATF-82x26-DT-10K	EATF-82x26-DTB-10K
EATF-82x20-DT-14K	EATF-82x20-DTB-14K
EATF-82x22-DT-14K	EATF-82x22-DTB-14K
EATF-82x24-DT-14K	EATF-82x24-DTB-14K
EATF-82x26-DT-14K	EATF-82x26-DTB-14K

PREMIUM ALUMINUM TRAILERS

Built for Work or Play

Available Sizes

Description	Payload	Dry Weight
EATF-82x20-DT-10K	8,170 lbs	1720 lbs
EATF-82x22-DT-10K	8,070 lbs	1820 lbs
EATF-82x24-DT-10K	7,970 lbs	1920 lbs
EATF-82x26-DT-10K	7,870 lbs	2020 lbs
EATF-82x20-DT-14K	12,080 lbs	1920 lbs
EATF-82x22-DT-14K	11,980 lbs	2020 lbs
EATF-82x24-DT-14K	11,880 lbs	2120 lbs
EATF-82x26-DT-14K	11,780 lbs	2220 lbs
EATF-82x20-DTB-10K	8,170 lbs	1720 lbs
EATF-82x22-DTB-10K	8,070 lbs	1820 lbs
EATF-82x24-DTB-10K	7,970 lbs	1920 lbs
EATF-82x26-DTB-10K	7,870 lbs	2020 lbs
EATF-82x20-DTB-14K	12,080 lbs	1920 lbs
EATF-82x22-DTB-14K	11,980 lbs	2020 lbs
EATF-82x24-DTB-14K	11,880 lbs	2120 lbs
EATF-82x26-DTB-14K	11,780 lbs	2220 lbs



ALL ALUMINUM CONSTRUCTION

Light • Strong • Durable

www.stronghaul.com

Standard Features

Frame: Aluminum 6061 (frame 8" x 3" x .25"w, hitch 6" x 2" .25"w, floor channels 3" x 1.5" x .19"w)

Dovetail: 2' with 3" drop (included in trailer length)

Axle -52: 5200lb Straight Slipper Leaf Spring, E-brake

Axle -70: 7000lb Straight Slipper Leaf Spring, E-brake

Axle Brackets: .250" Galvanized and Taped

Suspension: HD Slipper Style, Greaseable Equalizer

Harness Plug: 7-Way RV-Style Connector, Breakaway

Coupler: 2-5/16" Ball Coupler, Max rating 2,100lb tongue WT, with Polypropylene Tape

Tires -52: ST225/75R15 6-ply Radial

Tires -70: ST235/80R16 10-ply Radial

Wheels -52: Black Steel, R15", 6 lug on 5.5" BHP

Wheels -70: Black Steel, R16", 8 lug on 6.5" BHP

Lighting: LED Lighting Pkg with Sealed Harness

Jack: 9,500lb, Drop Leg with Removable Handle

Decking: 2x10 No. 1 Gr, Douglas Fir/Larch Planks

Safety Chains: 3/8" x 35" Chains, 16.2K lb Rating

Ramp, Bifold -B: Dual Beaver Tail, 8,000lb

Ramp, Pocket Style: 7,000lb

Stabilizer Stands: Fold Up, on Pocket Ramp Model

Spare Tire Mount: Front, or on side with toolbox

Lashing Rings: 4,000lb, ZP (8 rings on 20', 10 on 22'/24', 12' on 26' models)

Ground to Coupler Height: 16" Level (14" or 18" adj)

Deck to Ground Height: 26"

Stake Pockets, Side Rub Rails, Tip out Fenders

GVWR: 10,000lbs on -52

GVWR: 14,000lbs on -70

Available Options

Aluminum Wheel Upgrade PKG

Spare Wheel, Black Steel

Spare Wheel, Aluminum

Spray Shield, 27" Height from Deck

Stone Shield, Front Rail Cover

Extra Lashing Rings 4k lb

Recessed Lashing Rings 6k lb

Stabilizer Stands, Drop Leg

Winch Plate, 12" x 18"

Toolbox, A-Frame Mounted, Lockable



PREMIUM ALUMINUM TRAILERS

Built for Work or Play