



# FATD

## THE ALUMINUM ADVANTAGE

- ✓ Lightweight
- ✓ Fuel Economy
- ✓ Easier Handling
- ✓ Rust Resistant
- ✓ Paint Free
- ✓ Clean Aluminum Design



# FATD



Address: 139144 Road 11E  
Arborg, MB, Canada  
P.O. Box 269 R0C 0A0

[www.stronghaul.com](http://www.stronghaul.com)



# FATD

Flat deck Style, Aluminum Frame,  
Tandem, Deck over Axle Trailer



FATD-101x14-7K  
FATD-101x16-7K  
FATD-101x18-7K  
FATD-101x20-7K  
FATD-101x14-10K  
FATD-101x16-10K  
FATD-101x18-10K  
FATD-101x20-10K

**PREMIUM ALUMINUM TRAILERS**  
Built for Work or Play

**SMART DESIGN**  
Purpose Built • Work Ready

## Available Sizes

| Description     | Payload   | Dry Weight |
|-----------------|-----------|------------|
| FATD-101x14-7K  | 5,470 lbs | 1530 lbs   |
| FATD-101x16-7K  | 5,400 lbs | 1600 lbs   |
| FATD-101x18-7K  | 5,285 lbs | 1715 lbs   |
| FATD-101x20-7K  | 5,195 lbs | 1805 lbs   |
| FATD-101x14-10K | 8,205 lbs | 1685 lbs   |
| FATD-101x16-10K | 8,130 lbs | 1760 lbs   |
| FATD-101x18-10K | 8,020 lbs | 1870 lbs   |
| FATD-101x20-10K | 7,925 lbs | 1965 lbs   |



**ALL ALUMINUM CONSTRUCTION**  
Light • Strong • Durable  
[www.stronghaul.com](http://www.stronghaul.com)

## Standard Features

|                                                                                      |
|--------------------------------------------------------------------------------------|
| Frame: Aluminum 6061                                                                 |
| Rail Height: 13.5" (Deck to top of Rail)                                             |
| Axle -7K: 3500lb Straight, Leaf Spring, E-brake                                      |
| Axle -10K: 5200lb Straight, Leaf Spring, E-brake                                     |
| Axle Brackets: .250" Galvanized and Taped                                            |
| Harness Plug: 7-Way RV-Style Connector with Break-away Kit                           |
| Coupler: 2-5/16" Ball Coupler, Max rating 2,100lb tongue WT, with Polypropylene Tape |
| Tires -7K: ST205/75R15 6-ply Radial                                                  |
| Tires -10K: ST225/75R15 7-ply Radial                                                 |
| Wheels -7K: Black Steel, R15", 5 lug on 4.5" BHP                                     |
| Wheels -10K: Black Steel, R15", 6 lug on 5.5" BHP                                    |
| Lighting: LED Lighting Pkg with Sealed Harness                                       |
| Jack: 5,000lb, A-Frame Mounted                                                       |
| Decking: 2x10 No. 1 Gr, Douglas Fir/Larch Planks                                     |
| Safety Chains: 3/8" x 35" Chains, 16.2K lb Rating, with Safety Latch                 |
| Ramp, Pocket Style: 2,500lb, under rear of deck                                      |
| Spare Tire Mount: Front, or on side with toolbox                                     |
| Lashing Rings: 4,000lb, ZP (6 rings on 14', 6 on 16' models, 8 rings on 18' models)  |
| Ground to Coupler Height: 17" When Level                                             |
| Deck to Ground Height: 30"                                                           |
| Stake Pockets and Side Rub Rail all around                                           |
| GVWR: 7,000lbs on -7K                                                                |
| GVWR: 9,980lbs on -10K                                                               |

## Available Options

- Aluminum Wheel Upgrade PKG
- Spare Wheel, Steel
- Spare Wheel, Aluminum
- Extra Lashing Rings 4k lb
- Recessed Lashing Rings 6k lb
- Jack Caster Wheel
- Side Mount Pivot Jack
- Coupler, 2-5/16" Adjustable
- Front Rail Kit, Bolt In
- Toolbox, A-Frame Mounted, Lockable



**PREMIUM ALUMINUM TRAILERS**  
Built for Work or Play