

## EATD (10K or 14K GVW)

### Equipment Hauler, Aluminum Frame, Tandem, Deck Over Axle Trailer



#### -Standard Features and Equipment-

Deck Size: 102" W x 288" L (Ramps fold flat to increase deck length to 348")	Wheels: Black Modular Style Wheels, R16" x 8" W, 8 Lug on 6.5" BHP
Overall Size: 102" W x 425" L	Tires: Goodride or Westlake ST235/80R16 10-ply Radial Tires
GVWR: 14,000lbs (can be derated to 10,000lbs at time of registration)	Harness Plug: 7-Way RV-Style Connector with Break-away Kit
Stake Pockets: .250" Thick, Inner Measurements: 3.5"x1.5"	Lighting: LED Lighting Pkg with Sealed Harness
Rub Rail: .250" x 3.00" 6061-T6	Decking: 2x8 No.1 Grade, Douglas Fir/Larch Plank Floor
Winch track: Double L Winch Track	Safety Chains: 3/8" x 35" Chains, 16.2K lb. Rating, with Safety Latch
Hitch Length: 63" L	Spare Mount: A-Frame Spare Tire Mount
Front Guard: 8" Front Lip/ Stone Guard	Deck to GND Height: 35"
Suspension: 3,500lb HD Slipper Style Leaf Springs, Greaseable Equalizer	Top of Bumper to GND Height: 20"
Axles: 7000lb Straight, E-brake, Slipper Leaf Spring, Dexter Axles	Coupler to GND Height: 19" when Level
Axle Mounting Brackets: .250" Hangers & Main Brkt, Galv. with Poly Tape	Coupler: 2-5/16" Adjustable Ball Coupler, 8" of Adjustment with Poly Tape
Chain Tubes: 2.00" x .250" 6061-T6 Round Tubes	Beavertail: 5' Beavertail Section, 16" Drop (Trailer Length includes Beavertail)
Jack: 9,500lb, Drop Leg Jack with Removable Side Wind Handle	Deck Hatch: Rear Central Hatch, Lifts Between Ramps to be Level with Deck Surface
Frame Tubes: 8.00" x 3.00" x .250"w 6061-T6	Ramp Loading Angle: 15 Degrees
Hitch Tubes: 8.00" x 3.00" x .250"w 6061-T6	Ramps: Dual Flip Over Beaver Tail Ramps, 8,000lb CAP/Ea, 60" L x 32" W
Outer Frame Tubes: 5.00" x 2.00" x .190"w 6061-T6	Integrated Ramp Knee Brace, Spring Assisted
Crossmembers: 3.00" x 1.50" x .190"w 6061-T6 on 16" CTR's	

#### -Available Sizes-

Description	Payload	Dry Wt.
<a href="#">EATD-101x23-14K</a>	10,635 lbs	3,365 lbs
<a href="#">EATD-101x25-14K</a>	10,535 lbs	3,465 lbs
<a href="#">EATD-101x27-14K</a>	10,435 lbs	3,565 lbs
<a href="#">EATD-101x29-14K</a>	10,335 lbs	3,665 lbs

#### -Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Aluminum
Spare Wheel, Steel Black Modular Style
Extra Lashing Rings, 4k lb
Recessed Lashing Rings, 6k lb
Winch Plate, 12" x 18"
Toolbox, A-Frame Mounted with Lockable Handle