

Phone: (204) 364-2785 Email: sales@stronghaul.com

Address: 139144 Road 11E Arborg, MB, Canada

Box 269 R0C 0A0

UASR-DR (76x12 Displayed)

 $m{U}$ tility Style, $m{A}$ luminum Frame, $m{S}$ ingle Axle, $m{R}$ ailside Trailer with $m{D}$ rop in Side $m{R}$ amps





-Standard Features and Equipment-		
-6061 All Aluminum Frame	-2x10 Douglas Fir/Larch Plank Floor	
-13.5" Side Height (Deck to top of Rail)	-5/16" x 30" Safety Chains, 7.6K lb Rating, with Safety Latch	
-3500lb Drop Axle, Idler	-Folding Rear Ramp rated at 3000lbs	
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Ramp Unfolded Length: 54" L x 55" W (Ramp Width is trailer size - 5.00")	
-4-Pin Flat, Easy Pull Electrical Connector	-Ramp Folds Down onto Deck	
-2" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape	-Side Loading Access w/ Drop in Ramp Gates, 1250 lb Capacity/Ea, 61" L x 13" W	
-ST205/75R15 6-ply Radial Tires	-2,000lb Lashing Rings , ZP (8 rings on 12' models, and 10 on 14')	
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Spare Tire Mount (Changes from front to side depending on tool box)	
-LED Lighting Package	-Deck to Ground Height: 18"	
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-Ground to Coupler Height: 15" When Level	
-A-Frame Mounted Jack Rated at 5K lbs	-GVWR: 2,990lbs (3,500lbs with additional electric brake option)	

-Available Sizes-		
Description	STD. Payload	Dry Wt.
UASR-76x12-DR	2,100 lbs	890 lbs
UASR-76x14-DR	1,910 lbs	1080 lbs
UASR-82x12-DR	2,055 lbs	935 lbs
UASR-82x14-DR	1,975 lbs	1015 lbs

-Available Options-		
Description		
Aluminum Wheel Upgrade PKG		
Spare Wheel, Steel		
Spare Wheel, Aluminum		
Extra Lashing Rings 2k lb		
Jack Caster Wheel		
Side Mount Pivot Jack		
A-Frame Mounted, Lockable Handle Tool Box		
Electric Braking Axle Upgrade		