



Premium Aluminum Trailers, Built for Work or Play

Phone: (204) 364-2785

Email: sales@stronghaul.com

Address: 139144 Road 11E Arborg, MB, Canada

Box 269 R0C 0A0

UASS-24 (60x10 Displayed)

Utility Style, Aluminum Frame, Single Axle, Solid side Trailer with 24" Sides



-Standard Features and Equipment-

-6061 All Aluminum Frame	-2x10 Douglas Fir/Larch Plank Floor
-22.5" Side Height (Deck to top of Flange)	-5/16" x 30" Safety Chains, 7.6K lb Rating, with Safety Latch
-3500lb Straight Axle, Idler	-Folding Rear Ramp rated at 3000lbs
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Ramp Unfolded Length: 54" L x 55" W (Ramp Width is trailer size - 5.00")
-4-Pin Flat, Easy Pull Electrical Connector	-Ramp Folds Down onto Deck
-2" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape	-2,000lb Lashing Rings , ZP (4 rings on 8' models, 6 on 10', 8 on 12', and 10 on 14')
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"
-LED Lighting Package	-Ground to Coupler Height: 15" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 2,990lbs (3,500lbs with additional electric brake option)
-A-Frame Mounted Jack Rated at 5K lbs	

-Available Sizes-

Description	STD. Payload	Dry Wt.
UASS-60x10-24	2,315 lbs	675 lbs
UASS-60x12-24	2,280lbs	710 lbs
UASS-66x10-24	2,285 lbs	705 lbs
UASS-66x12-24	2,210 lbs	780 lbs
UASS-76x12-24	2,140 lbs	850 lbs

-Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Spray Shield, Solid Side, 60"
Spray Shield, Solid Side, 66"
Spray Shield, Solid Side, 76"
Extra Lashing Rings 2k lb
Jack Caster Wheel
Side Mount Pivot Jack
A-Frame Mounted, Lockable Handle Tool Box
Electric Braking Axle Upgrade