

## UATS-24 (76x12 Displayed)

Utility Style, Aluminum Frame, Tandem Axle, Solid side Trailer with 24" Sides



### -Standard Features and Equipment-

-6061 All Aluminum Frame	-A-Frame Mounted Jack Rated at 5K lbs
-22.5" Side Height (Deck to top of Flange)	-2x10 Douglas Fir/Larch Plank Floor
-Tandem 3500lb Drop Axles, Electric Brakes	-3/8" x 35" Safety Chains, 16.2K lb Rating, with Safety Latch
-Zinc-Plated Axle Mounting Brackets with Polypropylene Tape	-Folding Rear Ramp rated at 3000lbs
-7-Pin RV Style Electrical Connector	-Ramp Unfolded Length: 54" L x 71" W (Ramp Width is trailer size - 5.00")
-Junction Box, Break-away Kit with Battery and Charger	-Ramp Folds Down onto Deck
-2-5/16" Ball Coupler, Max 2,100lb tongue WT, with Polypropylene Tape	-4,000lb Lashing Rings, ZP (6 rings on 12' models, 6 on 14', 6 on 16', and 8 on 18')
-ST205/75R15 6-ply Radial Tires	-Spare Tire Mount (Changes from front to side depending on tool box)
-Modular-Style Steel Wheels, R15", 5 lug on 4.5" BHP, Black	-Deck to Ground Height: 18"
-LED Lighting Package	-Ground to Coupler Height: 15" When Level
-Enclosed Wiring, Protected with Tubing/Hose and Sealed with Silicone	-GVWR: 7000lbs

### -Available Sizes-

Description	Payload	Dry Wt.
<a href="#">UATS-76x12-24</a>	5,775 lbs	1225 lbs
<a href="#">UATS-76x14-24</a>	5,730 lbs	1270 lbs
<a href="#">UATS-76x16-24</a>	5,655 lbs	1345 lbs
<a href="#">UATS-82x14-24</a>	5,715 lbs	1285 lbs
<a href="#">UATS-82x16-24</a>	5,630 lbs	1370 lbs

### -Available Options-

Description
Aluminum Wheel Upgrade PKG
Spare Wheel, Steel
Spare Wheel, Aluminum
Spray Shield, Solid Side, 76"
Spray Shield, Solid Side, 82"
Extra Lashing Rings 4k lb
Recessed Lashing Rings 6k lb
Jack Caster Wheel
Side Mount Pivot Jack
Stabilizer Stands, Drop Leg
2-5/16" Adjustable Coupler
A-Frame Mounted, Lockable Handle Tool Box