



UASR-DR-5K

THE ALUMINUM ADVANTAGE

- ✓ Lightweight
- ✓ Fuel Economy
- ✓ Easier Handling
- ✓ Rust Resistant
- ✓ Paint Free
- ✓ Clean Aluminum Design



UASR-DR-5K



Address: 139144 Road 11E
Arborg, MB, Canada
P.O. Box 269 R0C 0A0

www.stronghaul.com



UASR-DR-5K

Utility Style, Aluminum Frame,
Single Axle, Railside Trailer, with
Drop in Side Ramps



UASR-76x12-DR-5K

UASR-76x14-DR-5K

UASR-82x12-DR-5K

UASR-82x14-DR-5K

PREMIUM ALUMINUM TRAILERS
Built for Work or Play

SMART DESIGN
Purpose Built • Work Ready

Available Sizes

Description	Payload	Dry Weight
UASR-76x12-DR-5K	4,310 lbs	890 lbs
UASR-76x14-DR-5K	4,120 lbs	1080 lbs
UASR-82x12-DR-5K	4,265 lbs	935 lbs
UASR-82x14-DR-5K	4,115 lbs	1085 lbs



ALL ALUMINUM CONSTRUCTION

Light • Strong • Durable

www.stronghaul.com

Standard Features

Frame: Aluminum 6061

Rail Height: 13.5" (Deck to top of Rail)

Axle: 5200lb Straight, E-brake

Suspension: 2,600lb Double Eye Style Leaf Springs

Axle Brackets: .250" Galvanized and Taped

Harness Plug: 7-Way RV-Style Connector with Break-away Kit

Coupler: 2-5/16" Ball Coupler, Max rating 700lb tongue WT, with Polypropylene Tape

Tires: 225/75R15 10-ply Radial

Wheels: Black Mod. Steel, R15", 6 lug on 5.5" BHP

Lighting: LED Lighting Pkg with Sealed Harness

Jack: 5,000lb, Drop Leg

Decking: 2x10 No. 1 Gr, Douglas Fir/Larch Planks

Safety Chains: 5/16" x 30" Chains, 7.6K lb Rating, with Safety Latch

Ramp: Bi-fold Ramp, Fold Down, 3,000lb

Ramp Unfolded Length: 54" L

Ramp Folds Down onto Deck

Lashing Rings: 2,000lb, ZP (8 on 12', 10 on 14')

Spare Tire Mount: Front, or on side with toolbox

Deck to Ground Height: 23"

Ground to Coupler Height: 18" When Level

GVWR: 5,200 LBS

Available Options

Aluminum Wheel Upgrade PKG

Spare Wheel, Steel

Spare Wheel, Aluminum

Extra Lashing Rings 2k lb

Jack Caster Wheel

Side Mount Pivot Jack

Toolbox, A-Frame Mounted, Lockable



PREMIUM ALUMINUM TRAILERS

Built for Work or Play