STRONGhaul
Aluminum Trailers

UATF-DT

THE ALUMINUM ADVANTAGE

- ✓ Lightweight
- ✓ Fuel Economy
- ✓ Easier Handling
- ✓ Rust Resistant
- ✓ Paint Free
- ✓ Clean Aluminum Design





SMART DESIGN
Purpose Built • Work Ready

STRONGhaul
Aluminum Trailers

UATF-DT





Address: 139144 Road 11E
Arborg, MB, Canada
P.O. Box 269 R0C 0A0

www.stronghaul.com

STRONGhaul
Aluminum Trailers

UATF-DT

Utility Style, Aluminum Frame, Tandem Axle, Flat Bed Trailer with 2' Dove Tail



UATF-82x16-DT-7K	UATF-82x16-DTB-7K
UATF-82x18-DT-7K	UATF-82x18-DTB-7K
UATF-82x20-DT-7K	UATF-82x20-DTB-7K
UATF-82x16-DT-10K	UATF-82x16-DTB-10K
UATF-82x18-DT-10K	UATF-82x18-DTB-10K
UATF-82x20-DT-10K	UATF-82x20-DTB-10K

PREMIUM ALUMINUM TRAILERS
Built for Work or Play

STRONGhaul
Aluminum Trailers

UATF-DT

Utility Style
Aluminum Frame
Tandem Axle
Flatbed Trailer with 2’ Dove Tail

Available Sizes

Description	Payload	Dry Weight
UATF-82x16-DT-7K	5,700 lbs	1300 lbs
UATF-82x18-DT-7K	5,595 lbs	1405 lbs
UATF-82x20-DT-7K	5,485 lbs	1515 lbs
UATF-82x16-DT-10K	8,440 lbs	1450 lbs
UATF-82x18-DT-10K	8,345 lbs	1545 lbs
UATF-82x20-DT-10K	8,255 lbs	1635 lbs
UATF-82x16-DTB-7K	5,705 lbs	1295 lbs
UATF-82x18-DTB-7K	5,605 lbs	1395 lbs
UATF-82x20-DTB-7K	5,480 lbs	1520 lbs
UATF-82x16-DTB-10K	8,440 lbs	1450 lbs
UATF-82x18-DTB-10K	8,330 lbs	1560 lbs
UATF-82x20-DTB-10K	8,220 lbs	1670 lbs



Standard Features

- Frame: Aluminum 6061
- Rail Height: 13.5“ (Deck to top of Rail)
- Axle -7K: 3500lb Straight, Leaf Spring, E-brake
- Axle -10K: 5200lb Straight, Leaf Spring, E-brake
- Axle Brackets: .250” Galvanized and Taped
- Harness Plug: 7-Way RV-Style Connector with Break-away Kit
- Coupler: 2-5/16" Ball Coupler, Max rating 2,100lb tongue WT, with Polypropylene Tape
- Tires -7K: ST205/75R15 6-ply Radial
- Tires -10K: ST225/75R15 7-ply Radial
- Wheels -7K: Black Steel, R15", 5 lug on 4.5" BHP
- Wheels -10K: Black Steel, R15", 6 lug on 5.5" BHP
- Lighting: LED Lighting Pkg with Sealed Harness
- Jack: 5,000lb, A-Frame Mounted
- Decking: 2x10 No. 1 Gr, Douglas Fir/Larch Planks
- Safety Chains: 3/8" x 35” Chains, 16.2K lb Rating, with Safety Latch
- Ramp, Bifold -B: Folding Rear Ramp rated at 3000lbs
- Ramp, Pocket Style: 2,500lb, under rear of deck
- Spare Tire Mount: Front, or on side with toolbox
- Lashing Rings: 4,000lb, ZP (6 rings on 16’ models, 8 rings on 18’, 20’ models)
- Ground to Coupler Height: 16" When Level
- Deck to Ground Height: 23"
- Stake Pockets, Side Rub Rails, Removable Fenders
- GVWR: 7,000lbs on -7K
- GVWR: 9,980lbs on -10K

Available Options

- Aluminum Wheel Upgrade PKG
- Spare Wheel, Steel
- Spare Wheel, Aluminum
- Spray Shield, 82”
- Stone Shield, Rail Cover, 15” x 82”
- Extra Lashing Rings 4k lb
- Recessed Lashing Rings 6k lb
- Jack Caster Wheel
- Side Mount Pivot Jack
- Stabilizer Stands, Drop Leg
- Coupler, 2-5/16” Adjustable
- Winch Plate, 12” x 18”
- Toolbox, A-Frame Mounted, Lockable



ALL ALUMINUM CONSTRUCTION
Light • Strong • Durable
www.stronghaul.com

PREMIUM ALUMINUM TRAILERS
Built for Work or Play